THE IDEAL MULTI-PURPOSE GROUND RESISTANCE

TESTER The Model 5004 is designed to measure the resistance of grounding electrodes or grids, utilizing the fall-of-potential test method. The Model 5004 is perfectly suited to perform soil- resistivity measurements, touch-potential measurements, touch/step potential measurements, and display earth-voltage readings. Phase-locked loop and switched-filter design allows for smooth operation even in electrically noisy environments. Standard features include a rugged aluminum alloy case, three resistance ranges, an earth voltage measurement function, four-pole terminal connections, line or battery power capability, and a direct reading digital display. The unit is supplied with a power cord for charging internal batteries, auxiliary electrodes, test cables and connectors for performing various types of tests, a manual and a NIST traceable certificate of calibration.

Model 5004
FOUR POLE
GROUND TESTER

FEATURES

Rugged, compact design
3 or 4 pole testing ability
Earth voltage testing mode
Line or battery operation
Active electrical-noise-suppression circuitry
Large LCD indications

SPECIFICATIONS

Resistance Ranges: $0-20\Omega$, $0-200\Omega$,

0-2000Ω

Resolution: To 0.001Ω

Test Current: 10 mA up to 20Ω . 1 mA

on 2000 Ω range.

Resistance Accuracy (percent of range): $0-20\Omega$, $\pm 3\%$ ± 1 digit $0-200\Omega$ and

 $0-2000\Omega$, $\pm 1.5\% \pm 1$ digit

AC Voltage Measurement Range: 0-19.99V, with 0.01V Resolution

Voltage Measurement Accuracy (percent of range): 1-19.99V, ±3% ±1 digit

Operating Environment: 32° to 104°F at ≤85% RH

Power supply: 120 VAC ±10%, 60 Hz or Eight (8) rechargeable AA Batteries

Weight: 3.1 lbs.

Dimensions: 8.7×7.9×4.2 inches



Amblyonix Model 5004 Four Pole Ground Tester

ORDERING INFORMATION

Supplied with rugged aluminum case, manual, interconnecting cable and ground cable.

1-year parts and labor warranty.



20 Republic Road, North Billerica, MA 01862 800-447-4020 WWW.AMBLYONIX.COM